

DRYTAC®



Ro//Lam Laminators

Drytac Europe Ltd
Filwood Road
Fishponds
Bristol
BS16 3RY
United Kingdom

Tel: +44(0)117 958 6500
Web: www.drytac.co.uk

Drytac Europe Limited is pleased to offer this new range of German designed **Ro//Lam** laminators exclusively in the UK and Ireland. The **Drytac Ro//Lam** laminator cold pressure sensitive range offer's versatility for the mounting and laminating of posters, art prints, inkjet-media etc. The range of **Drytac Ro//Lam 1200W**, **Ro//Lam 1400W** and **Ro//Lam 1600W** models are equipped with a heater, making it possible to heat the silicone roller to approximately 30°C-60°C, resulting in a higher quality of laminations for vinyl's and are ideal for vehicle wraps & graphics for the outdoor signage market.

The pressure is adjusted by only one handle which guarantees an even pressure on the whole width of the roller. A photocell provides security and switches off the machine if used improperly. A further feature are the unroll and upwind axes with practically proved quick gripping cones by which the material rolls can be changed easily. The running speed is continuously adjustable. The machines can be operated either by control panel or by pedal and have forward and reverse movement.

Laminators



The laminators of the C-series are pure cold laminators. A warming-up of the upper roller is not possible.

Technical specifications

Model	Ro//Lam 1200C	Ro//Lam 1400C	Ro//Lam 1600C
Working width / Roller width	1200 mm / 1300 mm	1400 mm / 1500 mm	1600 mm / 1700 mm
Width / depth / height	1700 / 680 / 1210 mm	1900 / 680 / 1210 mm	2100 / 680 / 1210 mm
Height of front worktable	875 mm	875 mm	875 mm
Weight	168 kg	188 kg	218 kg
Max. board thickness	25 mm	25 mm	25 mm
Diameter of rollers	112 mm	112 mm	130 mm
Max. speed	3.5 m/min	3.5 m/min	4 m/min
Voltage	230V / 0.07 KW	230V / 0.07 KW	230V / 0.07 KW
Adjustment of height	central	central	central
Finger protection	yes	yes	yes
Foot switch	yes	yes	yes
Unroll and upwind axis (at the top)	yes	yes	yes
Unroll axis (at the bottom)	yes	yes	yes
Quick gripping cones	yes	yes	yes
Forward and reverse action	yes	yes	yes
Speed adjustable	yes	yes	yes
CE-certificate	yes	yes	yes

Laminators



The upper roller of the models **Ro//Lam 120W**, **Ro//Lam 140W** and **Ro//Lam 160W** is equipped with a thermoelement what makes it possible to heat the silicone roller to approx. 30°C-60°C.

Technical specifications

Model	<i>Ro//Lam 1200W</i>	<i>Ro//Lam 1400W</i>	<i>Ro//Lam 1600W</i>
Thermoelement	30°C-60°C	30°C-60°C	30°C-60°C
Working width / Roller width	1200 mm / 1300 mm	1400 mm / 1500 mm	1600 mm / 1700 mm
Width / depth / height	1700 / 680 / 1210 mm	1900 / 680 / 1210 mm	2100 / 680 / 1210 mm
Height of front worktable	875 mm	875 mm	875 mm
Weight	168 kg	188 kg	218 kg
Max. board thickness	25 mm	25 mm	25 mm
Diameter of rollers	112 mm	112 mm	130 mm
Max. speed	3.5 m/min	3.5 m/min	4 m/min
Voltage	230V / 0.9 KW	230V / 1.0 KW	230V / 1.3 KW
Adjustment of height	central	central	central
Finger protection	yes	yes	yes
Silicone rollers	yes	yes	yes
Foot switch	yes	yes	yes
Unroll and upwind axis (at the top)	yes	yes	yes
Unroll axis (at the bottom)	yes	yes	yes
Quick gripping cones	yes	yes	yes
Forward and reverse action	yes	yes	yes
Speed adjustable	yes	yes	yes
CE-certificate	yes	yes	yes

Accessories

Take up unit – backside



The take up unit with slipping clutch is mounted on the backside of the machine and allows working from “roll to roll”.

Product
Take up unit for <i>Ro//Lam</i> 1200C / 1200W
Take up unit for <i>Ro//Lam</i> 1400C / 1400W
Take up unit for <i>Ro//Lam</i> 1600C / 1600W

Take up unit – front side



The take up unit with slipping clutch is mounted on the front side of the machine and allows laminating on both sides.

Product
Take up unit for <i>Ro//Lam</i> 1200C / 1200W
Take up unit for <i>Ro//Lam</i> 1400C / 1400W
Take up unit for <i>Ro//Lam</i> 1600C / 1600W

Accessories

Front media holder



The front media holder made of canvas lightens the handling of the print media.

Product
Front media holder for <i>Ro//Lam</i> 1200C / 1200W
Front media holder for <i>Ro//Lam</i> 1400C / 1400W
Front media holder for <i>Ro//Lam</i> 1600C / 1600W

Unroll axes



In case of working with several different films or rather films in different width a frequent change-over can be avoided by additional unroll axes.

Product
Unroll axis with quick gripping cones for <i>Ro//Lam</i> 1200C / 1200W
Unroll axis with quick gripping cones for <i>Ro//Lam</i> 1400C / 1400W
Unroll axis with quick gripping cones for <i>Ro//Lam</i> 1600C / 1600W

Cleaning supplies

RollClean	Agent for a thorough cleaning of silicone and rubber rollers. Ideal for the removal of impurities of all kinds, especially glue remains.
Code	Content
71.004.000	500 ml